

METRA HIT 1A and METRA HIT 2A

Analog Multimeters

3-349-304-03
3/4.16

- Voltage measurement:** 0...0.15, 0...0.5 V=, 0 ... 1.5, 5, 15, 50, 150, 500 V=/~
- Input resistance:** 20 kΩ/V=, 4 kΩ/V~
- Current measurement:** 0 ... 50 μA=, 0 ... 0.5, 5, 50, 500 mA, 5 A=/~
- Extended current measurement, METRA HIT 2A:** ... 15 A=/~
- Resistance measurement:** 1 Ω ... 1 MΩ (4 ranges)
- Capacitance:** 200 mF ... 2 μF (4 ranges)
- Level:** -15 ... +56 dB (6 ranges)



5 Ampere

15 Ampere / Class 2.5

500 V CAT II
IEC/EN 61010-1, Second Edition



Broad Range of Applications

A large number of measuring ranges allows for universal use of the instruments, for example in electronics, digital technology and a wide variety of general electrical applications.

Safety Features

The connector jacks and plugs included with the measurement cables which are available as accessories are protected against inadvertent contact.

Measuring Range Selector Switch

All measuring ranges are selected with a rotary switch.

Rugged Mechanical Design

The rugged plastic housing and the spring loaded bearing jewels in the moving-coil mechanism protect the instrument from damage due to mechanical stressing. Especially effective protection is provided by the protective rubber cover and the ever-ready case, both of which are available as accessories.

Characteristic Values

Voltage Measuring Ranges

Voltage	Output ¹⁾	Internal Resistance, Approx.	
		—	~
0.15 V —	—	3.15 kΩ	—
0.50 V —	—	10.00 kΩ	—
1.50 V ≈	-15 ... + 6 dB	31.50 kΩ	6.50 kΩ
5.00 V ≈	-5 ... + 16 dB	100.00 kΩ	20.00 kΩ
15.00 V ≈	+5 ... + 26 dB	315.00 kΩ	65.00 kΩ
50.00 V ≈	+15 ... + 36 dB	1.00 MΩ	200.00 kΩ
150.00 V ≈	+25 ... + 46 dB	3.15 MΩ	650.00 kΩ
500.00 V ≈	+35 ... + 56 dB	10.00 MΩ	2.00 MΩ

¹⁾ 0 dB ≈ 0.775 V in the 1.5 V ~ range, 0 dB ≈ 1 mW to 600 Ω
Voltage related input resistance:
for —: 20.0 kΩ/V
for ≈: 4.0 kΩ/V

METRA HIT 1A: Current Measuring Ranges

Current	Voltage Drop, Approx.	
	—	~
50.00 μA —	0.158 V	—
0.50 mA ≈	1.15 V	1.00 V
5.00 mA ≈	1.25 V	1.25 V
50.00 mA ≈	1.25 V	1.25 V
500.00 mA ≈	1.85 V	1.85 V
5000.00 mA ≈	1.73 V	1.73 V

Applicable Regulations and Standards

IEC/EN 61010-1/ VDE 0411-1	Safety requirements for electrical equipment for measurement, control and laboratory use
EN 60529 VDE 0470, part 1	Test instruments and test procedures, degrees of protection provided by enclosures (IP code)
DIN EN 61326-1 VDE 0843-20-1	Electrical equipment for control technology and laboratory use – EMC requirements

METRA HIT 1A and METRA HIT 2A

Analog Multimeters

METRA HIT 2A: Current Measuring Ranges

Current	Voltage Drop, Approx.	
	—	~
50 µA —	0.158 V	—
1.5 mA ~	1.16 V	1.21 V
15 mA ~	1.25 V	1.25 V
150 mA ~	1.25 V	1.25 V
1.5 A ~	1.95 V	1.95 V
15 A ~	0.43 V	0.49 V

Resistance Measuring Ranges

Resistance	Scale Span	Value at Scale Middle (R_i)	Max. Measuring Current $I_{max}^{2)}$, Approx.
Ω x 1	1 Ω ... 1 kΩ	18.00 Ω	83 mA
Ω x 10	10 Ω ... 10 kΩ	180.00 Ω	8.3 mA
Ω x 100	100Ω ... 100 kΩ	1.80 kΩ	0.83 mA
Ω x 1000	1kΩ ... 1 MΩ	18.00 kΩ	0.083 mA

²⁾ At a battery voltage of 1.5 V

Capacitance Measuring Ranges

Capacitance ³⁾	Scale Span
µF x 1000	2000 ... 200000 µF
µF x 100	200 ... 20000 µF
µF x 10	20 ... 2000 µF
µF x 1	2 ... 200 µF

³⁾ Rough measurements in the resistance measuring ranges, determination of measured values with comparative scale

Reference Conditions

Ambient temperature +23°C ±2 K

Normal position of use Horizontal

Frequency 40 ... 60 Hz

Line Voltage For ~: sinusoidal

Relative humidity 40 ... 60%

The instrument is equipped with half-wave rectification and is RMS calibrated. It evaluates the arithmetic mean value of a half-wave and displays different values for pulsating voltage and current depending upon polarity.

Other influencing quantities: per IEC/EN 60 051

Ambient Conditions

Storage temp. range -25 to 65° C (without battery)

Relative humidity Up to 75%, no condensation allowed

METRA HIT 2A: Accuracy

(under reference conditions per IEC/EN 60 051)

Class 2.5 for — and ~, max. additional intrinsic error in the 15 A~ range: ±2%; in the 1.5 V~ range: +1/-2.5%, class 2.5 for Ω (error relative to 52 mm scale length)

METRA HIT 2A: Additional accuracy class influence and Nominal Ranges of Use

Ambient temp. For —: 0 ... +23 ... +40° C
For ~: +13 ... +23 ... +35° C

Frequency 1.5 ... 500 V ranges:
35 ... 40 ... 60 ... 1000 Hz
1.5 mA ... 1.5 A ranges:
35 ... 40 ... 60 ... 1000 Hz
15 A range:
40 ... 45 ... 60 ... 1000 Hz

Other influencing quantities: per IEC/EN 60 051

Power Supply

Battery for resistance measurement

One 1.5 V mignon cell per IEC LR6/R6 (size AA), leak-proof

Electrical Safety

Safety class

II per IEC 61010-1:2010/
DIN EN 61010-1:2011/
VDE 0411-1:2011

Measuring category II

500 V

3.5 kV~

Fouling factor 2

Replaceable

METRA HIT 1A:

F1: FF630mA/700V AC (50 kA), 6.3 x 32

F2: FF6.3A/500V AC (50 kA), 6.3 x 32

METRA HIT 2A:

F1: FF1.6A/700V AC (50 kA), 6.3 x 32

F2: FF16A/500V AC (50 kA), 6.3 x 32

Soldered permanently into place
750 mA / 600 V AC

METRA HIT 1A: Overload Capacity

Range	To
0.15 V —	20 V ¹⁾ ≈
0.5 V —	50 V ²⁾ ≈
1.5 V —	100 V ²⁾ ≈
5.0 V —	150 V ²⁾ ≈
15.0 V —	250 V ²⁾ ≈
50.0 V —	250 V ²⁾ ≈
150.0 V —	300 V ²⁾ ≈
500.0 V —	500 V ²⁾ ≈
50.0 µA —	1.0 mA ≈
0.5 mA —	5.0 mA ≈
5.0 mA —	10.0 mA ≈
50.0 mA —	70.0 mA ≈
500.0 mA —	500.0 mA ≈
5000.0 mA —	3.0 A ≈
	5.0 A ³⁾ ≈

Range	To
—	—
—	25 V ²⁾ ≈
1.5 V ~	50 V ²⁾ ≈
5.0 V ~	150 V ²⁾ ≈
15.0 V ~	250 V ²⁾ ≈
50.0 V ~	300 V ²⁾ ≈
150.0 V ~	500 V ²⁾ ≈
—	—
0.5 mA ~	5.0 mA ≈
5.0 mA ~	10.0 mA ≈
50.0 mA ~	70.0 mA ≈
500.0 mA ~	500.0 mA ≈
5000.0 mA ~	3.0 A ≈
	5.0 A ³⁾ ≈

METRA HIT 2A: Overload Capacity

Range	To
0.15 V —	20 V ¹⁾ ≈
0.5 V —	50 V ²⁾ ≈
1.5 V —	100 V ²⁾ ≈
5.0 V —	150 V ²⁾ ≈
15.0 V —	250 V ²⁾ ≈
50.0 V —	250 V ²⁾ ≈
150.0 V —	300 V ²⁾ ≈
500.0 V —	500 V ²⁾ ≈
50.0 µA —	1.0 mA ≈
1.5 mA —	5.0 mA ≈
15 mA —	20.0 mA ≈
150 mA —	150.0 mA ≈
1.5 A —	1.2 A ≈
	1.5 A ³⁾ ≈
15 A —	12.0 A ≈
	15.0 A ³⁾ ≈

Range	To
—	—
—	25 V ²⁾ ≈
1.5 V ~	50 V ²⁾ ≈
5.0 V ~	150 V ²⁾ ≈
15.0 V ~	250 V ²⁾ ≈
50.0 V ~	300 V ²⁾ ≈
150.0 V ~	500 V ²⁾ ≈
—	—
1.5 mA ~	5.0 mA ≈
15 mA ~	20.0 mA ≈
150 mA ~	150.0 mA ≈
1.5 A ~	1.2 A ≈
	1.5 A ³⁾ ≈
15 A ~	12.0 A ≈
	15.0 A ³⁾ ≈

¹⁾ Fuse F1 blows in the event of overloading.

²⁾ Ranges are protected against overloading with PTC resistor

³⁾ Max. 1 minute

METRA HIT 1A and METRA HIT 2A

Analog Multimeters

Electromagnetic Compatibility (EMC)

Interference emission EN 61326:2006 class B
 Interference immunity EN 61326:2006
 EN 61326-2-1:2006

Mechanical Design

Scale length	A, V – 0 ... 5.0: approx. 83 mm A, V – 0 ... 15.8: approx. 77 mm A, V~ 0 ... 5.0: approx. 67 mm A, V~ 0 ... 15.8: approx. 59 mm $\Omega \infty$... 0: approx. 52 mm dB – 15 ... +6: approx. 42 mm
Dimensions	92 x 126 x 45 mm
Weight	Approx. 0.3 kg without battery
Protection	Housing: IP 40, terminals: IP 20 per EN 60529/VDE 0470, part 1

Table Excerpt Regarding Significance of the IP Code

IP XY (1 st digit, X)	Protection against penetration of solid particles	IP XY (2 nd digit, Y)	Protection against penetration by water
0	Not protected	0	Not protected
1	≥ 50.0 mm dia.	1	Vertical dripping
2	≥ 12.5 mm dia.	2	Dripping (15° inclination)
3	≥ 2.5 mm dia.	3	Spray water
4	≥ 1.0 mm dia.	4	Splashing water
5	Dust protected	5	Jet-water
6	Dust-proof	6	Powerful water jets

Standard Equipment

- 1 analog multimeter (without battery or cable set)
- 1 set operating instructions

Accessories

F809 Ever-Ready Case with Cable Compartment – For tabletop operation – The cover can be snapped to the bottom of the case when using the shoulder strap.



METRA HIT 1A and METRA HIT 2A

Analog Multimeters

Current Measuring Accessories									Suitable for METRA HIT	
Type	Designation	Measuring Range	Measur- ing Cat.	Max. to Wire Dia.	Transformation Ratio	Frequency Range	Intrinsic Error \pm (% rdg. + ...)	Article Number	1A	2A
AC Current Transformer with Current Output										
WZ12A	Clip-on current transformer	15 ... 180 A~	300 V / CAT III	15 mm	1 mA/A	<u>45 ... 65</u> ... 400 Hz	3%	Z219A	●	●
WZ12D	Clip-on current transformer	30 mA ... 150 A~	300 V / CAT III	15 mm	1 mA/A	<u>45 ... 65</u> ... 500 Hz	2.5% +0.1 mA	Z219D	As of 5 A	As of 5 A
Z3511	Clip-on current transformer	4 ... 500 A~	600 V / CAT III	30 x 63 mm	1 mA/A	<u>48 ... 65</u> ... 1 kHz	3% +0.4 A	GTZ3511 000R0001	As of 50 A	As of 50 A
Z3512	Clip-on current transformer	0.5 ... 1000 A~	600 V / CAT III	52 mm	1 mA/A	<u>30...48 ... 65</u> ... 5 kHz	0.5% ... 0.7%	GTZ3512 000R0001	As of 50 A	As of 0 A
Z3514	Clip-on current transformer	1 ... 2000 A ~	600 V / CAT III	64 x 150 mm	1 mA/A	<u>30...48 ... 65</u> ... 5 kHz	0.5% +0.1 A	GTZ3514 000R0001	As of 500 A	As of 500 A

● Without restriction

WZ12 Clip-On Current Transformer



SM16 Current Measuring Adapter



KS17-2 Cable Set

Cable set with permanently mounted test probes and contact-protected angle plugs for safe measuring. Hook clips, alligator clips or push-on lugs can be attached to the test probes for special measuring tasks.



Edited in Germany • Subject to change without notice • A pdf version is available on the internet



GMC-I Messtechnik GmbH
Südwestpark 15
90449 Nürnberg • Germany

Phone +49 911 8602-111
Fax +49 911 8602-777
E-Mail info@gossenmetrawatt.com
www.gossenmetrawatt.com